

# SW7.5ABF



**Input: 230 – 400 – 500 Vac**  
**Output: 24 Vdc 60°C**  
**Efficiency up to 89%**  
**Strong overload without switch-off, up to 50%**  
**Flexible Power continuity: from 120 to 180 W**  
**“Power Good” Relay**  
**Three mode of output protections:**  
**1)Hiccup mode**  
**2)Continuous Out Mode**  
**3)Manual Reset**  
**DIN Rail Mountable**  
**Extremely small size**  
**3 Years warranty**

## Input Data

Nominal Input Voltage (2 x Vac)	230 – 400 – 500 Vac
Manual select Input from 230 to 400-500	
Input Voltage range: (230)	187-264 Vac
(400-500)	330-550 Vac 462-770 Vdc
Inrush Current (Vn and In Load)	≤ 28 A ≤ 5 msec.
Frequency	47 -63 Hz
Input Current (230 – 400 – 500 Vac)	1.45 – 0.83 – 0.68 A
Internal Fuse	T 4 A
External Fuse (recommended)	10 A (MCB curve B)

## Output Data

Output Voltage (Vn) Factory Setting ±3%	24 Vdc
Adjustment range (Vadj)	22 – 27 Vdc
Start up with Strong Load (capacitive load)	≤50.000µF
Turn-On delay after applying mains voltage	1 sec. (max)
Continuous Current at 24 V < 40°C (In)	7.5 A
Continuous Current at 24 V < 50°C (In)	6 A
Continuous Current at 24 V < 60°C (In)	5 A
Power Boost Current at 24 Vdc 60°C(In)	In (60°C) x 1.5 3 min.
Current max. Overload ≈ 4Vdc (permanent)	I <sub>max</sub> =In60°Cx(1.8 - 2.2)
Maximum Short Circuit Current I <sub>cc</sub>	16 A
Hiccup mode: Max 2 sec. Continuous Mode	Typ. 20 msec
Hold-up Time ( min. Vac) Vn In 40°C	≤ 80 mVpp
Residual Ripple	≥ 89 %
Efficiency	Yes. Shut-down output and automatic restart.
Over temperature Protection	1° Manual Reset
	2° Hiccup Mode
	3° Continuous Out Mode
Short-circuit protection	22 W
	Yes
Max Dissipation Power at Vn In 40°C	Yes (typ. 35 Vdc)
Over Load protection	Yes
Over Voltage Output protection	Resistive load
Parallel connection	Min permissive load
Power Good Contact rating (EN60947.4.1):	
Max. DC1: 30 Vdc 1 A; AC1: 60 Vac 1A	
Min.1mA at 5 Vdc	

## Climatic Data

Ambient Temperature operation	-25 up to +70 °C (>60°derating 2.5% °C)
Ambient Temperature Storage	-40 up to +85 °C
Humidity at 25 °C, no condensation	95 % to 25 °C

## General Data

Isolation Voltage (In / Out)	3000 Vac
Isolation Voltage (In / PE)	1605 Vac
Isolation Voltage (Out / PE)	500 Vac
Protection Class (EN/IEC 60529)	IP 20
Reliability: MTBF IEC 61709	> 500.000 h
Pollution Degree Environment	2
Connection Terminal Blocks Screw Type	2,5 mm <sup>2</sup> (24 – 14 AWG)
Protection class	I with PE connected
Dimension (w-h-d)	55x110x105 mm
Weight	0.60 kg approx.

## Norms and certifications

The CE mark in According to EMC 2014/30/UE and Low voltage directive 2014/35/UE.

## Electrical Safety

In compliance to EN IEC 61010-2-201:2018

According to IEC/EN 60950 (VDE 0805) e EN 50178 (VDE 0160) for assembling device. The unit must be installed according to IEC/EN 60950.Input / Output separation: SELV EN60950-1 and PELV EN 60204-1. Double or reinforced insulation.

## EMC Immunity

EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN61000-6-2

## EMC Emission:

EN61000-6-4, EN61000-3-2

## Standards Conformity

EN 60204-1 Safety of Electrical Equipment Machines

